



Models

Colour Temperature	Ref:
 Warm White 2800K - 3200K	519-1231
 Cool White 4000K - 4500K	519-1232
 Daylight 5000K - 5500K	519-204926
 Daylight 6000K - 6500K	519-1233

Technical Details

Power:	24 W	IP Protection:	IP20
Voltage:	220-240V AC	Material:	Aluminium
Multi-Voltage:	85-265V AC	Installation:	Surface
Frequency:	50-60 Hz	Size:	40xØ300 mm
Driver Output:	30-38V DC // 550-600 mA	Height:	40 mm
Protection Class:	II	Diameter:	Ø300 mm
Light Source:	OSRAM	Total Weight:	0.72 Kg
CRI:	80	Frame:	White
Lumens:	1900 lm	Working Temperature:	-22°C ~ +45°C
Energy Efficiency 2021 (UE-1369/2017):	A	Includes:	Driver
Energy Efficiency 2023 (UE-2019/2015):	F	Life Span:	40,000 Hours
Beam Angle:	120°	Warranty:	3 Years
Lens Type:	Frost	Certifications:	CE & RoHS, UKCA
Use:	Indoor		



Description

This Round 24W LED Surface Panel Ø295 mm combines design, power and an extremely low consumption into a luminaire that's very easy to install.

It can easily replace a conventional 150W surface panel and **is highly recommendable for use in any area of the home or office, hotel receptions and bars**. It stands out for its light quality, which reproduces colours as they appear naturally and also shows off the items high Colour Rendering Index.

Advantages of this Round 24W LED Surface Panel Ø295 mm

The main advantages are the **high savings in consumption and maintenance** that it provides. It's a simple installation and only requires two screws to hold the support found on the back of the unit onto the ceiling. It's connected directly to the mains using the driver that's included.



Additional photographs

