






## Models

Colour Temperature	Ref:
 Daylight 4000K	63931-125100
 Cool White 6500K	63931-125103
 Warm White 3200K	63931-130795

## Technical Details

<b>Power</b>	5 W
<b>Tension</b>	220-240V AC
<b>Frequency</b>	50-60 Hz
<b>Electric Insulation Class</b>	II
<b>Light Source</b>	SMD2835
<b>Color Rendering Index (CRI)</b>	80
<b>Brightness</b>	500 lm
<b>Luminous Efficiency</b>	100 lm/W
<b>Use</b>	Indoor
<b>IP Protection</b>	IP40

<b>Material</b>	Pc
<b>High</b>	35 mm
<b>Wide</b>	22 mm
<b>Lenght</b>	305 mm
<b>Useful life</b>	40,000 Hours
<b>Selectable Opening Angle</b>	120
<b>Light color</b>	Warm White, Cool White, Daylight
<b>Color Temperature</b>	3200K, 6500K, 4000K
<b>Energy Efficiency 2023 (EU-2019/2015)</b>	F



## Description

The **300mm 5W Batten with integrated T5 LED Tube and Switch** offers a lighting solution that combines quality and substantial energy and maintenance savings. The product incorporates a connector to connect several strips in series. It is recommended to join up to a maximum of 5 strips to form a chain of 1.5 meters in length.

**It offers very homogeneous lighting thanks to the 120° opening angle of the light beam. The opal finish of the luminaire reduces glare.** It has an aluminium housing and a cover made of PC (polycarbonate), materials resistant to water, dust and corrosion. It has a connecting cable to feed the strip. Its driver is integrated inside the strip.

The 300mm 5W Batten with integrated T5 LED Tube and Switch is ideal for replacing traditional terminal blocks and for installation in a wide range of facilities such as factories, warehouses, car parks, tunnels, niches or terraces



## Additional photographs

