



Models

Colour Temperature	Ref:
 Warm White 2800K - 3200K	516-1216
 Cool White 4000K - 4500K	516-1217
 Daylight 5000K - 5500K	516-205001
 Daylight 6000K - 6500K	516-1218

Technical Details

Power:	48 W	IP Protection:	IP20
Power Factor:	0.90	Material:	Aluminium
Voltage:	220-240V AC	Installation:	Surface
Multi-Voltage:	85-265V AC	Size:	35x600x600 mm
Frequency:	50-60 Hz	Height:	35 mm
Protection Class:	II	Width:	600 mm
Light Source:	OSRAM	Length:	600 mm
CRI:	80	Frame:	White
Lumens:	3800 lm	Working Temperature:	-22°C ~ +45°C
Energy Efficiency 2021 (UE-1369/2017):	A	Includes:	Driver
Energy Efficiency 2023 (UE-2019/2015):	F	Life Span:	40,000 Hours
Beam Angle:	120°	Warranty:	3 Years
Lens Type:	Frost	Certifications:	CE & RoHS, UKCA
Use:	Indoor		



Description

This **Square 48W LED Surface Panel 600x600 mm** is easy to install on any type of ceiling, be it plaster, concrete or any other surface. It has a 120° opening angle and provides a very evenly distributed light.

Recommended for buildings that are either under construction or have just been completed, they can replace existing light bulbs in homes, offices, waiting rooms, bars, etc.

Includes Driver.

Dimmable.

To dim this panel, purchase the corresponding dimmable driver.



Additional photographs

