



Models

Power	Ref:
40 W	65705-131250



Technical Details

Frequency	50-60 Hz	High	21 mm
Electric Insulation Class	II	Wide	30 mm
Use	Indoor	Lenght	355 mm
IP Protection	IP20	Brand	LIFUD
Flicker	No Flicker	Power	40 W
Material	Pc, Aluminum		



## Description

Driver made by the prestigious company **LIFUD**, specially designed for emergency situations where it is necessary that, in case of a power failure, it fulfills the lighting requirements in normal and emergency situations. To determine whether a driver will work with our luminaires, PCBs or panels, please consult the voltage and output current of the driver.

### Characteristics of the 100-277V LIFUD Flicker-Free Emergency Driver 30-40V Output 1000mA 40W LF-GSP040YD

This **40W 30-40V DC Output Flicker-Free LIFUD Emergency Driver** has a multi-voltage input. This means that it is able to withstand line voltage surges and dips for a short period of time without damage. In addition, **its output is 30V-40V DC 1000mA in Normal Mode and 30-40V DC 350mA in Emergency Mode.**

When there is a power failure, this emergency driver switches to emergency mode and provides **60 to 90 minutes** of illumination depending on the power of the luminaire.

For perfect operation, this product should be powered by a 18V DC LITHIUM Emergency Driver Battery (not included).

This LIFUD Driver features Flicker-Free technology, preventing light flicker and therefore reducing eye fatigue.

Say goodbye to eye fatigue, headaches and blurred vision caused by flickering light.



## Additional photographs

