



Models

Colour Temperature	Ref:
 Blanco Cálido 2900K - 3200K	1143-2129
 Cool White 4000K - 4500K	1143-2128
 Daylight 6000K - 6500K	1143-2127

Technical Details

Power:	24 W
Voltage:	220-240V AC
Multi-Voltage:	85-265V AC
Frequency:	50-60 Hz
Protection Class:	II
Light Source:	OSRAM
CRI:	80
Lumens:	1900 lm
Energy Efficiency 2021 (UE-1369/2017):	A
Energy Efficiency 2023 (UE-2019/2015):	F
Beam Angle:	120°
Lens Type:	Frost
Use:	Indoor

IP Protection:	IP20
Material:	Aluminium
Installation:	Surface
Size:	44xØ300 mm
Height:	44 mm
Diameter:	Ø300 mm
Frame:	Silver
Working Temperature:	-22°C ~ +45°C
Includes:	Driver
Life Span:	40,000 Hours
Warranty:	3 Years
Certifications:	CE & RoHS, UKCA



Ambience





Description

The 24W Silver Metal Round LED Surface Panel Ø300 mm reunites power and design, providing us with a very high quality luminaire.

It uses high performance SMD2835 LEDs that **provide a brightness of 1,900 lumens**, similar to that which is emitted by a fluorescent 48W surface panel but with a 50% reduction in consumption when compared with a low-consumption unit.

As it has a 120° opening angle, this 24W Round Design Silver Metal LED Surface Panel Ø300 mm **is used for general lighting in all sorts of indoor spaces**. The installation of these LED units is very simple, just attach it to any surface using the screws and as it has class II isolation, an earth connection is not required.



Additional photographs

