




Models

Colour Temperature	Ref:
 Warm White 2700K - 3200K	406-766
 Daylight 4000K - 4500K	406-767
 Cool White 6000K - 6500K	406-768
 Cool White 5000K - 5500K	406-205026

Technical Details

Power	12 W	Material	Aluminum
Tension	220-240V AC	Installation	Surface
Rated Voltage	85-265V AC	High	40 mm
Frequency	50-60 Hz	Wide	170 mm
Electric Insulation Class	II	Lenght	170 mm
Adjustable	No	Room Temperature Work	-22 °C~+45 °C
Light Source	OSRAM	Includes	Driver
Color Rendering Index (CRI)	80	Useful life	40,000 Hours
Brightness	880 lm	Selectable Opening Angle	120
Type of Lens	Frost	Light color	Daylight, Warm White, Cool White
Use	Indoor	Color Temperature	4000K - 4500K, 2700K - 3200K, 5000K - 5500K, 6000K - 6500K
IP Protection	IP20	Energy Efficiency 2023 (EU-2019/2015)	F



Description

This Square 18W LED Surface Panel 170x170 mm, whose main feature is its ease of installation on any type of ceiling, be it plaster, concrete or any other surface, has a 120° opening angle and provides a very evenly distributed light.

Recommended for buildings that are either under construction or have just been completed, they can replace existing light bulbs in homes, offices, waiting rooms, bars, etc.

Includes Driver.

Dimmable.

To dim this panel, purchase the corresponding dimmable driver.



Additional photographs

