



## Models

Colour Temperature	Ref:
<input checked="" type="checkbox"/> No Flicker Warm White 3000K	1355-173092
<input type="checkbox"/> No Flicker Cool White 4000K	1355-173098
<input type="checkbox"/> No Flicker Daylight 6000K	1355-173104

## Technical Details

<b>Power:</b>	24 W
<b>Power Factor:</b>	0.96
<b>Voltage:</b>	220-240V AC
<b>Multi-Voltage:</b>	85-265V AC
<b>Frequency:</b>	50-60 Hz
<b>Screw:</b>	T8
<b>Light Source:</b>	EPISTAR SMD2835
<b>CRI:</b>	80
<b>Lumens:</b>	2880 lm
<b>LED Performance:</b>	120 lm/W
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A+
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F
<b>Beam Angle:</b>	180°

<b>Lens Type:</b>	Frost
<b>Use:</b>	Indoor
<b>IP Protection:</b>	IP44
<b>Special:</b>	High Brightness
<b>Material:</b>	PC, Aluminium
<b>Size:</b>	1500xØ30 mm
<b>Length:</b>	1500 mm
<b>Diameter:</b>	Ø30 mm
<b>Total Weight:</b>	0.3 kg
<b>Working Temperature:</b>	-20°C ~ 45°C
<b>Life Span:</b>	50,000 Hours
<b>Warranty:</b>	3 Years
<b>Certifications:</b>	CE & RoHS, UKCA



## Description

**This 150cm 5ft 24W T8 G13 LED Tube with One Side Power is enough to replace a fluorescent 48W tube.**

Its LEDs have a 100lm/W performance and **the light emitted is of the highest quality, distributed over a 180° beam angle**. The frosted diffuser it includes allows the light to be distributed in a more uniform manner, reducing possible glare.

Featuring an IP44 Protection factor, this 150cm 5ft 24W T8 G13 LED Tube with One Side Power is the **perfect element for installations in humid areas**. This tube is wired direct to the mains via the end which says 'input' and does not require a ballast or starter to function.

Discover the best lighting on the market with our 150cm 5ft 24W T8 G13 LED Tube with One Side Power, available here at LEDKIA, our online lighting shop.

\*Includes a LED Starter

\*T8 LED Tube Installation Guide



## Additional photographs

