



Models



Technical Details

| | |
|--------------------------|--------------|
| Maximum Power: | 1200 W |
| Voltage: | 220-240V AC |
| Frequency: | 50-60 Hz |
| Protection Class: | II |
| Beam Angle: | 360° |
| Use: | Indoor |
| IP Protection: | IP20 |
| Material: | Fireproof PC |
| Colour: | White |
| Installation: | Surface |
| Size: | 58xØ120 mm |

| | |
|-----------------------------|-----------------|
| Height: | 58 mm |
| Diameter: | Ø120 mm |
| Total Weight: | 0,135 kg |
| Frame: | White |
| Detector: | PIR |
| Detection Distance: | 3-6 m |
| Detection Angle: | 360° |
| Working Temperature: | -20°C ~ +40°C |
| Warranty: | 3 Years |
| Certifications: | CE & RoHS, UKCA |



Description

This ceiling mounted PIR Motion Sensor has a 360° coverage angle and a 6 metre detection radius when at a height of 2.2 to 4 metres. It's capable of detecting infrared emissions from any heat source without emitting any radiation.

The detector activates its output circuit when a heat source moves in front of the switch and deactivates when the heat is no longer detected and some time has passed.

Detection Angle: 360°

Detection Distance: 3 to 6 metres.

Minimum ON time: 10 seconds \pm 3 seconds.

Maximum ON time: 7 minutes \pm 2 minutes.

Installation Height: 2.2 to 4 metres.

Detection Speed: 0.6-1.5 m/s.

Charges: 300W LED and 1200W Incandescent.



Additional photographs

