



## Models

Colour Temperature

Ref:

☐ Cool White 4000K - 4500K

61139-119533



## Technical Details

<b>Power:</b>	3 W
<b>Voltage:</b>	220-240V AC
<b>Multi-Voltage:</b>	85-265V AC
<b>Frequency:</b>	50-60 Hz
<b>Light Colour:</b>	Cool White
<b>CRI:</b>	80
<b>Lumens:</b>	300 lm
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F
<b>Beam Angle:</b>	120°
<b>Use:</b>	Indoor
<b>IP Protection:</b>	IP20

<b>Material:</b>	Aluminium
<b>Installation:</b>	Recessed
<b>Size:</b>	20xØ83 mm
<b>Cut-Out</b>	Ø69 mm
<b>Height:</b>	20 mm
<b>Diameter:</b>	Ø83 mm
<b>Frame:</b>	White
<b>Working Temperature:</b>	-20°C / +100°C
<b>Includes:</b>	Driver
<b>Life Span:</b>	40,000 Hours
<b>Warranty:</b>	3 Years
<b>Certifications:</b>	CE & RoHS, UKCA



## Description

The **Round 3W LED Panels** stands out for being **extremely thin** as well as for its **high quality finish and modern design**. Given its performance, it is perfect to replace a 24W halogen luminaire.

### Features of the Round 3W LED Panels

With an integrated light source that provides a **high quality light**, distributed at a **beam angle of 120° for ample and effective lighting**. In addition, it is capable of providing a **brightness of 300 lumens at an output of only 3W**.

It is **made of aluminium, which, together with the incorporated diffuser** contributes to improving the durability of the luminaire.

### Advantages of the Round 3W LED Panels

The main advantage of this type of LED lighting is its **compact size**, which allows the user to install it in false ceilings, even if there is limited space.

**Drastically reduce the cost of the electricity bill as well as maintenance cost and replacement lights** thanks to its reduced consumption.

Given the power and performance of this LED panel, it is the ideal LED lighting element for corridors, hallways, staircases or for spaces where a wide range of ambient light is required



## Additional photographs

