



## Models

Colour

 Black

Ref:

15100-31750



## Technical Details

<b>Material:</b>	PE	<b>Air Temp. For Operation:</b>	-10 °C / +125°C
<b>Diameter:</b>	24 mm	<b>Warranty:</b>	3 Years
<b>Length:</b>	1 m	<b>Certifications:</b>	CE



## Description

The Polyethylene heat-shrink tube has a **high shrinkage ratio of 3:1 (24-8mm)** and is 1 meter in length. It is ideal to cover irregular or complex shapes thanks to its capacity to shrink to a third of its original size. The adhesive liner in this tube, when melted, provides a watertight seal, which encapsulates the cable joints.

Applications include the following:

- Applications include the following:
- Watertight encapsulation and sealing of cable joints.
- Electrical insulation.
- Environmental protection against moisture, dust and chemicals.
- Mechanical protection against abrasion on cables and small parts.
- Pulling protection at cable and connector joints to prevent damage caused by bending.
- Bundling and organisation of cables and tubes. Colour coding of cables and components.
- They do not act as a means of fire propagation.
- The fumes emitted are transparent and therefore do not obstruct vision.
- They do not cause irreversible damage to the health of persons exposed to the combustion gases of the cables for twenty minutes.



## Additional photographs

