



Models

Colour Temperature	Ref:
<input type="checkbox"/> Cool White 4000K	34764-73617
<input type="checkbox"/> Daylight 5000K	34764-122943



Technical Details

Power:	60 W	IP Protection:	IP66
Power Factor:	0.98	Material:	Glass, Aluminium
Voltage:	220-240V AC	Size:	130x250x500 mm
Frequency:	50-60 Hz	Height:	130 mm
Driver Output:	43-86V DC // 700-1400mA	Width:	250 mm
Protection Class:	I	Length:	500 mm
Light Source:	LUMILEDS SMD3030	Dimensions of the Base:	Ø65 mm
Number of LEDs:	96	Life Span:	100,000 Hours
Lumens:	7800 lm	Warranty:	3 Years
Luminous Efficiency:	130 lm/W	Certifications:	CE & RoHS, UKCA
Use:	Outdoor		



Description

The **60W Mini City LUMILEDS 3030 OSRAM Driver TYPE II-M Asymmetric** is a luminaire for public and street lighting. It offers instant start-up and high power. It is the ideal replacement for the old discharge streetlights, improving the quality of light and significantly reducing energy consumption.

Characteristics of the 90W City LUMILEDS 3030 OSRAM Driver TYPE II-M Asymmetric LED Street Light

Made of die-cast aluminium, it contains an inner hinge and an outer closing flange to improve its aesthetics and functionality. It is equipped with a multiLED optic protected by tempered glass and has a **90° adjustable head that makes it ideal for installation on columns or arms at any angle of inclination**. Its IP66 protection factor is ideal for outdoors, withstanding adverse weather conditions.

Equipped with the latest lighting technologies, this street light is **fitted with high-power LUMILEDS SMD3030 LEDs, which provide high light output**. In addition, the luminaire is equipped with a **surge protector** for greater safety.

LUMILEDS is a company that develops, manufactures and distributes lighting and holds more than 200 patents related to LED technology.

* Mounting diameters: from Ø45mm ~ Ø65mm



Additional photographs

