






### Models

Colour Temperature	Ref:
 Warm White 3000K	5658-14128
 Cool White 4000K	5658-12741
 Daylight 6000K	5658-14129



### Technical Details

Power:	15 W
Power Factor:	0.99
Voltage:	220-240V AC
Multi-Voltage:	85-265V AC
Frequency:	50-60 Hz
Intensity Level:	0.078 A
Screw:	2G11
Light Source:	SMD2835
Number of LEDs:	96
Lumens:	1620 lm
Luminous Efficiency:	90 lm/W
Energy Efficiency 2023 (UE-2019/2015):	F

Beam Angle:	180°
Lens Type:	Frost
Use:	Outdoor, Indoor
IP Protection:	IP44
Material:	PC, Aluminium
Size:	410x36x28 mm
Height:	28 mm
Width:	36 mm
Length:	410
Life Span:	40,000 Hours
Warranty:	3 Years
Certifications:	CE & RoHS, UKCA



## Description

**The 41 cm 15W 2G11 PLL LED tube is perfect for changing conventional fluorescent tubes in your home or business.**

The lumens provided by your SMD source are enough to replace 40W fluorescent tubes. This efficiency **provides us with a saving of 50%** compared to this type of technology. The 2G11 PLL LED tube of 41 cm and 15W **comes with an opal closure.**

The connection is made on its only side. **Its direct connection to the network allows eliminating the residual consumption of reactances and starters** , allowing greater durability and less maintenance. The 2G11 PLL 41 cm 15W LED Tube turns on instantly and without flicker effect (light flicker). **The heat sink is made of pure aluminum. These tubes are widely used in office parabolic luminaires and kitchen luminaires.**



## Additional photographs

