





## Models

Colour Temperature	Ref:
Warm White 3000K - 3500K	3620-8183
Daylight 4000K	3620-8184
Cool White 6000K	3620-8185

## **Technical Details**

Power	100 W
Tension	220-240V AC
Frequency	50-60 Hz
Electric Insulation Class	I
Adjustable	No
Light Source	SMD2835
Brightness	10000 lm
<b>Luminous Efficiency</b>	100 lm/W
<b>LED Performance</b>	120 lm/W
Type of Lens	Transparent
Use	Outdoor
IP Protection	IP65
IK Protection	IK08
Material	Aluminum, Crystal

Installation	Surface
High	220 mm
Wide	300 mm
Lenght	48 mm
Weight	1.96 kg
Room Temperature Work	-20 °C~+45 °C
Useful life	60.000 Hours
Certificates	RoHS, CE, UKCA
Warranty	3 Years
Selectable Opening Angle	110°
Light color	Warm White, Cool White, Daylight
Color Temperature	3000K - 3500K, 6000K, 4000K
Energy Efficiency 2023 (EU- 2019/2015)	F





## **Description**

This White 100W UltraSlim LED Floodlight stands out for its compact design and minimalist finish.

Characteristics of this White 100W UltraSlim LED Floodlight

This White 100W UltraSlim LED Floodlight is small and has modern and functional design.

Its SMD2835 optic is very efficient. The light is distributed over a 110° angle and is perfect for lighting in all sorts of settings. **It offers** considerable energy savings.

It's designed for lighting outdoor areas **and has IP65 Protection**. It's made of high quality aluminium, which can contribute to efficiently eliminating heat that is generated.

Applications for this White 100W UltraSlim LED Floodlight

It's mainly used on balconies, terraces and gardens, where we want to reduce energy consumption without sacrificing light quality.

Enjoy this White 100W UltraSlim LED Floodlight at the best price at LEDKIA, our online lighting shop.

\*This product is pre-wired with a 300mm cable. approximately.





## Additional photographs

o Ledkía.

