





Models

Colour Temperature		Ref:
	Super Warm White 1700K	62326-156423
	Warm White 2800K - 3200K	62326-122306

Technical Details

Power:	13.6 W/m	Beam Angle:	120°
Cut every:	10 cm	Use:	Indoor, Outdoor
Led Strip Installation:	MAX. 10 m	IP Protection:	IP65
Voltage:	24V DC	Material:	Silicone, Epoxy Resin, PCB
Dimmable:	Controller	Size:	3x10x5000 mm
Light Source:	SMD5050	Height:	3 mm
Number of LEDs:	300	Width:	10 mm
Light Colour:	Warm White, Daylight, Cool White	Length:	5000 mm
CRI:	80	Length:	5 m
Lumens:	1320 lm/m	Working Temperature:	-20°C ~ +50°C
Luminous Efficiency:	100 lm/W	Life Span:	40,000 Hours
Energy Efficiency 2021 (UE-1369/2017):	A+	Warranty:	3 Years
Energy Efficiency 2023 (UE-2019/2015):	F	Certifications:	CE & RoHS, UKCA



Description

The 5m 24V DC 60LED/m IP65 LED Strip 10mm Wide is one of the most widespread options for decorative or accent lighting with low power consumption. Its flexible design can be used in any location to add a special touch to any room.

Features of the 5m 24V DC 60LED/m IP65 LED Strip 10mm Wide

The 5m 24V DC 60LED/m IP65 LED Strip 10mm Wide integrates 300 high-efficiency SMD5050 LEDs that consume only 13 watts per meter. The bright and colorful emitted light is distributed at an angular aperture of 120°. A power supply is required to operate.

The electrical components in the LED Strip are covered with epoxy resin. It is perfectly protected against impact and moisture which contributes to **its IP65 protection factor and makes this type of LED lighting perfect not only for indoor but also for outdoor use.** It has a lifespan of approximately 30,000 hours.

Advantages of the 5m 24V DC 60LED/m IP65 LED Strip 10mm Wide

Thanks to its extra flat design, this type of LED lighting achieves ideal lighting effect for all types of projects with minimal visual impact. In addition, the **strip includes a 3M adhesive strip that simplifies installation on virtually any surface.**

The versatility of 5m 24V DC SMD5050 60LED/m IP65 LED Strip 10mm Wide allows for a variety of applications, such as accent lighting, decorative lighting or path illumination. It can be used in spaces such as facades, gazebos, corridors, showcases, shelves, etc.

*For correct operation and to avoid incidents, the connections must be protected with an insulating element against humidity and water.

*Never turn on the LED strips when they are coiled, this could cause overheating and burn the LEDs.



Additional photographs

