



### Models

Colour

Multi Coloured

Ref:

6832-15818



### Technical Details

<b>Brand</b>	3M	<b>Colour</b>	Multi Coloured
--------------	----	---------------	----------------



## Description

This 3M SFTW-202A MultiColor Heatshrink Tubing Kit (6x Diameters) **is made up of Polyolefin heatshrink tubes with 6x different diameters**. The compression relation is 2:1, the minimum compression temperature is 135°C, the working temperature is between -55°C and +135°C. It complies with RoHS requirements and is free of Halogen and PBDE.

It has a high resistance to chemical agents. It's capable of complying with the most strict industrial demands, be them aerospace, military, high sea or sea-faring, it's ideal for identification tasks and it the preferred heatshrink tube in most industries. **Sizes from 1.6mm to 9.5mm.**

It complies with strict VG 95343, UL 224 regulations and other international rules. VG 95343/5 A and B / PANAIA 6493 \* / UL-224 125 °C 600 V, Archive E48398 / German military certificate (BWB) K16/99085+99086 / Certificate VDE 94972 / SAE-AMS-DTL 23053/5 class 1 / IEC 60684-3-212:2005 / Det Norske Veritas E-6933 \* (\*except transparent).

### Ø Start of Tube mm / Ø End of Tube mm

<b>3.2</b>	<b>/</b>	<b>1.6</b>
<b>4.8</b>	<b>/</b>	<b>2.4</b>
<b>6.4</b>	<b>/</b>	<b>3.2</b>
<b>9.5</b>	<b>/</b>	<b>4.8</b>
<b>12.7</b>	<b>/</b>	<b>6.4</b>
<b>19</b>	<b>/</b>	<b>9.5</b>

Reference: KT-3M-7000037646



## Additional photographs

