





## Models

Colour Temperature		Ref:
	Cool White 6000K	65132-173437
	Daylight 4000K - 4500K	65132-173441

## Technical Details

<b>Power</b>	36 W
<b>Tension</b>	220-240V AC
<b>Rated Voltage</b>	100-265V AC
<b>Frequency</b>	50-60 Hz
<b>Electric Insulation Class</b>	II
<b>Adjustable</b>	No
<b>Color Rendering Index (CRI)</b>	80
<b>Brightness</b>	3240 lm
<b>Luminous Efficiency</b>	90 lm/W
<b>Type of Lens</b>	Frost
<b>Use</b>	Indoor, Outdoor
<b>IP Protection</b>	IP65
<b>IK Protection</b>	IK04

<b>Material</b>	Pc
<b>Installation</b>	Surface
<b>High</b>	75 mm
<b>Wide</b>	75 mm
<b>Lenght</b>	1200 mm
<b>Weight</b>	1.13 kg
<b>Useful life</b>	40,000 Hours
<b>Selectable Opening Angle</b>	120
<b>Tube Length</b>	120 cm
<b>Light color</b>	Daylight, Cool White
<b>Color Temperature</b>	4000K - 4500K, 6000K
<b>Energy Efficiency 2023 (EU-2019/2015)</b>	F



## Description

**1200mm** rectangular **Waterproof LED Screen** design, of **power 36W**. It offers optimum results both in terms of lighting and waterproofing, thanks to its resistant **materials to water, dust and corrosion, with an IP65 protection factor**. It has a **PC housing and a PC cover**. It is ideal for replacing conventional displays with 70W fluorescent tubes.

The design and characteristics of the LED Waterproof Display make it **ideal to install in a wide range of facilities such as factories, warehouses, car parks, tunnels, terraces... as well as places with humidity**.



## Additional photographs

