



Models

Colour	Ref:
Black	6831-15817

Technical Details

Warranty:	3 Years	Brand:	3M
Certifications:	CE & RoHS, UKCA		



Description

The 3M SFTW-202A Black Heatshrink Tubing Kit (6x Diameters) **is a kit that consists of heat shrinkable polyolefin tubes with 6 different diameters.** It has a compression ratio of 2:1, with a minimum compression temperature of 135 °C and its operating temperature has a range of -55 °C to +135 °C. It complies with RoHS requirements and is halogen and PBDE free.

It has good resistance to chemicals. It is capable of meeting the most demanding demands of the aerospace, military, offshore and railway industries, is ideal for identification tasks and is the preferred heat shrink tubing for most industries. **Sizes from 1.6mm to 9.5mm**

Meets the strict requirements of VG 95343, UL 224 and other international standards. VG 95343/5 A and B / PANAIA 6493 * / UL-224 125 °C 600 V, File E48398 / German Military Certificate (BWB) K16/99085+99086 / VDE Certificate 94972 / SAE-AMS-DTL 23053/5 class 1 / IEC 60684-3-212:2005 / Det Norske Veritas E-6933 * (*except transparent)

Ø Initial Tube mm / Ø End Tube mm

3.2	/	1.6
4.8	/	2.4
6.4	/	3.2
9.5	/	4.8
12.7	/	6.4
19	/	9.5

Reference: KT-3M-7000037645



Additional photographs

