



Models

Colour Temperature	Ref:
<input type="checkbox"/> Cool White 4000K	64916-126908
<input checked="" type="checkbox"/> Daylight 6000K	64916-126904

Technical Details

Power:	48 W	Beam Angle:	120°
Power Factor:	0.94	Lens Type:	Frost
Voltage:	220-240V AC	Use:	Indoor, Outdoor
Frequency:	50-60 Hz	IP Protection:	IP65
Intensity Level:	0.22 A	IK Protection:	IK04
Protection Class:	I	Material:	PC
Light Source:	EPISTAR SMD2835	Installation:	Surface
Number of LEDs:	264	Size:	1500x66x58 mm
CRI:	70	Working Temperature:	-20°C ~ +40°C
Lumens:	3930 lm	Life Span:	50,000 Hours
Energy Efficiency 2021 (UE-1369/2017):	A+	Warranty:	2 Years
Energy Efficiency 2023 (UE-2019/2015):	F	Certifications:	CE & RoHS, UKCA



Description

The **150cm 48W LED Slim Tri-Proof Light** is perfect as a replacement for a conventional **40W fluorescent tube**, which allows for 50% savings compared to the conventional luminaire.

Features of 150cm 48W IP65 LED Slim Tri-Proof Light

The LEDs use SMD2835 technology and along with its 0.94 power factor driver achieves superb luminous efficiency. It is distributed over an opening angle of 120°. Both the housing and the cover of the **Slim Tri-Proof Light** are made of **polycarbonate, which is a robust material that can withstand high levels of water, dust and corrosion**. All this is summarized in the IP65 and IK04 protection index.

Applications of 150cm 48W IP65 LED Slim Tri-Proof Light

The design and characteristics of this Tri-Proof Light make it the **perfect solution for the lighting of large and diverse interior spaces, such as factories, warehouses, parking lots, tunnels, terraces...** as well as places where there is humidity.



Additional photographs

