







## Models

| Colour Temperature       | Ref:       |
|--------------------------|------------|
| Warm White 2700K - 3200K | 218-453    |
| Cool White 6000K - 6500K | 218-454    |
| Daylight 4000K - 4500K   | 218-1467   |
| Cool White 5000K - 5500K | 218-204914 |

## **Technical Details**

| Power                          | 6 W         |
|--------------------------------|-------------|
| Tension                        | 220-240V AC |
| Rated Voltage                  | 85-265V AC  |
| Frequency                      | 50-60 Hz    |
| Electric Insulation            | n<br>II     |
| Adjustable                     | No          |
| Light Source                   | OSRAM       |
| Color Rendering<br>Index (CRI) | 80          |
| Brightness                     | 426 lm      |
| Use                            | Indoor      |
| IP Protection                  | IP20        |
| IK Protection                  | IK05        |
| Material                       | Aluminum    |
| Installation                   | Recessed    |

| High                                  | 20 mm                                 |
|---------------------------------------|---------------------------------------|
| Diameter                              | 117 mm                                |
| Room Temperature Work                 | -30 °C~+50 °C                         |
| Includes                              | Driver                                |
| Useful life                           | 40,000 Hours                          |
| Selectable Opening Angle              | 120                                   |
| Minimum Driver Tension                | 14 V                                  |
| Maximum Driver Tension                | 36 V                                  |
| Maximum Driver Intensity              | 300 mA                                |
| Light color                           | Cool White, Daylight, Warm White      |
| Color Temperature                     | 5000K - 5500K, 4000K - 4500K, 6000K - |
|                                       | 6500K, 2700K - 3200K                  |
| Energy Efficiency 2023 (EU-2019/2015) | F                                     |
| Revisión Control de Calidad           | No                                    |
|                                       |                                       |





## **Description**

The Round 6W UltraSlim LED Panel stands out for being extremely thin, perfect when there is no space available in the ceiling to install more bulky solutions.

It integrates an SMD 2835 light source that provides us with high quality light that is distributed at an angle of 120°. Given its performance, it is perfect for replacing a halogen luminaire of up to 35W. It has a life span of 30,000 hours.

Advantages of the Round 6W UltraSlim LED Panel

The main advantage of this type of LED lighting is its small size, which allows us to install it in false ceilings, even if there is hardly any space. At the same time, its reduced consumption and durability allow us **to drastically reduce the amount of the light bill and the costs of maintenance** and replacement of the lights.

Enjoy the SuperSlim 6W circular LED board at an unbeatable price and with a two-year guarantee, only at our online lighting shop Ledkia.





## Additional photographs

