



## Models

Number of Poles	Ref:
2P + PE	36304-75994
3P + N + PE	36304-76021

## Technical Details

<b>Frequency:</b>	50-60 Hz
<b>Input:</b>	Cable Gland
<b>Intensity Level:</b>	32 A
<b>Protection Class:</b>	I
<b>Use:</b>	Indoor, Outdoor
<b>IP Protection:</b>	IP66

<b>IK Protection:</b>	IK08
<b>Material:</b>	Technopolymer
<b>Working Temperature:</b>	-20°C ~ +45°C
<b>Warranty:</b>	3 Years
<b>Certifications:</b>	CE & RoHS, UKCA
<b>Brand:</b>	Scame



## Description







connector plug allows you to connect your load or receiver to an industrial type plug, commonly used in secondary or manufacturing sector.

**This device complies** with the European standards EN 60309-1-2, EN 60309-1-2/A1, EN 60309-1-2/A2 and **supports a nominal intensity of up to 32 A. It has an IP protection factor against dust and water of IP66 assuring optimal performance.**

**The most frequent applications** and use for these type of products (plugs, sockets, bases, frames, etc.) extend to industrial environments such as **chemical industries, agriculture, construction, shipyards, sports facilities, public events, the food industry, airports, port areas and water treatment, etc.** In all these environments it is necessary to use **products with great durability, reliability, ease of wiring, high degree of IP and IK protection and optimum resistance to atmospheric agents and chemicals.**

For the insertion of the conductor cable, these plugs and sockets use screw terminals, screw clamps and spring terminals depending on the application of the product. Cable clamps with tulip locks are used to secure the cables, guaranteeing water-tightness and safety. **In general they guarantee safe and optimal use in the most adverse conditions.**

It complements the electrical installation of any space. Take a look at our wide range of different sockets, consumer units, adapters and electrical material available at LEDKIA.

### Wiring Operations

Nominal Intensity (A)

Minimum Pin Size

Mobile Extenders

and socket connector (mm<sup>2</sup>)

Maximum Pin Size

Mobile Extenders

and socket connector (mm<sup>2</sup>)

Minimum Size, Fixed Base (mm<sup>2</sup>)

Maximum Size, Fixed Base (mm<sup>2</sup>)

External Diameter Min. cable gland (mm)

External Diameter Max. cable gland (mm)

16

1

2,5

1,5

4

8

15

32

2,5

6

2,5



### Additional photographs

