







## Models

Colour Temperature	Ref:
 Warm White 2700K - 3200K	219-442
 Cool White 4000K	219-1587
 Daylight 5000K - 5500K	219-205020
 Daylight 6000K - 6500K	219-443



## Technical Details

<b>Power:</b>	12 W	<b>IK Protection:</b>	IK05
<b>Voltage:</b>	220-240V AC	<b>Flicker Free:</b>	YES
<b>Multi-Voltage:</b>	85-265V AC	<b>Material:</b>	Aluminium
<b>Frequency:</b>	50-60 Hz	<b>Installation:</b>	Recessed
<b>Intensity Level:</b>	0.09 A	<b>Size:</b>	20xØ168 mm
<b>Protection Class:</b>	II	<b>Cut-Out</b>	Ø155 mm
<b>Light Source:</b>	OSRAM	<b>Height:</b>	20 mm
<b>Light Colour:</b>	Daylight, Cool White, Warm White	<b>Diameter:</b>	Ø168 mm
<b>CRI:</b>	80	<b>Total Weight:</b>	0.19 kg
<b>Lumens:</b>	960 lm	<b>Frame:</b>	White
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A+	<b>Working Temperature:</b>	-22°C ~ +45°C
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F	<b>Includes:</b>	Driver
<b>Beam Angle:</b>	120°	<b>Life Span:</b>	40,000 Hours
<b>Lens Type:</b>	Frost	<b>Warranty:</b>	3 Years
<b>Use:</b>	Indoor	<b>Certifications:</b>	CE & RoHS, UKCA
<b>IP Protection:</b>	IP20		



## Description

**The Round 12W UltraSlim LED panel has an innovative and modern design** with a white lacquered aluminium finish.

The 960 lumens provided by its LEDs are comparable to the luminosity of an energy-saving downlight of about 100W. This means that we obtain a 50% reduction in electricity consumption. **Its high colour rendering index of over 80 ensures correct colour reproduction.**

Applications of the Round 12W UltraSlim LED Panel

This type of LED **lighting is used for general lighting, mainly in the domestic environment**, although it can be used in commercial spaces without problems. It offers a very homogeneous light thanks to its wide opening angle and its opal diffuser, which reduces glare and reflections.

Enjoy the Round 12W UltraSlim LED Panel in a **choice of cold, neutral or warm white colour temperatures.**



## Additional photographs

