



Models

Number of Poles	Ref:
2P + PE	36394-76237
3P + PE	36394-76246
3P + N + PE	36394-76255

Technical Details

Frequency:	50-60 Hz
Intensity Level:	32 A
Protection Class:	I
Use:	Indoor, Outdoor
IP Protection:	IP54
IK Protection:	IK08

Material:	Technopolymer
Installation:	Surface
Working Temperature:	-20°C ~ +45°C
Warranty:	3 Years
Certifications:	CE & RoHS, UKCA
Brand:	Scame



Description







allows you to connect your load or receiver to an industrial type plug, commonly used in secondary or manufacturing sector. **It is specially designed to be surface mounted.**

This device complies with the European standards EN 60309-1-2, EN 60309-1-2/A1, EN 60309-1-2/A2 **supports a nominal intensity of up to 32 A** and has **a degree of protection against dust and water with an IP protection factor of IP54.**

The most frequent applications and use for these type of products (plugs, sockets, bases, frames, etc.) extend to industrial environments such as **chemical industries, agriculture, construction, shipyards, sports facilities, public events, the food industry, airports, port areas and water treatment, etc.** In all these environments it is necessary to use **products with great durability, reliability, ease of wiring, high degree of IP and IK protection and optimum resistance to atmospheric agents and chemicals.**

For the insertion of the conductor cable, these plugs and sockets use screw terminals, screw clamps and spring terminals depending on the application of the product. Cable clamps with tulip locks are used to secure the cables, guaranteeing water-tightness and safety. **In general they guarantee safe and optimal use in the most adverse conditions.**

It complements the electrical installation of any space. Take a look at our wide range of different sockets, consumer units, adapters and electrical material available at LEDKIA.

Wiring Operations

Nominal Intensity (A)

Minimum Pin Size

Mobile Extenders

and socket connector (mm²)

Maximum Pin Size

Mobile Extenders

and socket connector (mm²)

Minimum Size, Fixed Base (mm²)

Maximum Size, Fixed Base (mm²)

External Diameter Min. cable gland (mm)

External Diameter Max. cable gland (mm)

16

1

2,5

1,5

4

8

15

32

2,5

6

2,5



Additional photographs

