




## Models

Colour Temperature	Ref:
 Warm White 3000K - 3500K	63928-183040
 Cool White 4000K - 4500K	63928-125092
 Daylight 5500K - 6000K	63928-125096



## Technical Details

<b>Power:</b>	100 W	<b>IP Protection:</b>	IP65
<b>Power Factor:</b>	0.97	<b>FHSINST:</b>	Less than 0,1%
<b>Voltage:</b>	220-240V AC	<b>Material:</b>	Aluminium, Glass
<b>Frequency:</b>	50-60 Hz	<b>Colour Code:</b>	RAL 7035
<b>Driver Output:</b>	22-35V DC	<b>Size:</b>	505x215x80 mm
<b>Intensity Level:</b>	1500mA	<b>Height:</b>	505 mm
<b>Protection Class:</b>	I	<b>Width:</b>	215 mm
<b>Light Source:</b>	LUMILEDS SMD3030	<b>Length:</b>	80 mm
<b>Number of LEDs:</b>	120	<b>Fixing Diameter:</b>	Ø60 mm
<b>Lumens:</b>	13500 lm	<b>Total Weight:</b>	2.78 Kg
<b>Luminous Efficiency:</b>	135 lm/W	<b>Life Span:</b>	60,000 Hours
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A++	<b>Warranty:</b>	3 Years
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	E	<b>Certifications:</b>	CE & RoHS, UKCA
<b>Use:</b>	Indoor, Outdoor	<b>Brand Component</b>	LUMILEDS



## Description

The **Grey 100W Harlem 135lm/W LUMILEDS LED Street Light** is specially designed for street lighting.

**Its 3030SMD light source produces a luminous intensity of 13500 lumens.** The light it emits is brilliant and of high quality and is distributed at an **opening angle of 70-140°**. It is the perfect replacement for old discharge lamps, improving visibility on any type of road and reducing electricity consumption significantly.

Manufactured in injected aluminium and glass, the **Grey 100W Harlem 135lm/W LUMILEDS LED Street Light** has an **IP65 protection** factor that makes it resistant to the elements and an anti-corrosion treatment, both chemical and mechanical, resistant to UV rays that further improves its durability. Its life span is 30,000 hours.

Reducing energy consumption means significant savings for any urban centre. Enjoy the best road lighting with the **Grey 100W Harlem 135lm/W LUMILEDS LED Street Light** from our online shop Ledkia.

\* Fixing diameter: ~ Ø60mm

\*Compatible with the 90° Ø60mm Adjustable Support for Street Lighting

\*Wall bracket not included



## Additional photographs

