



Modellen

Stroomsterkte	Ref:
50 A	1014-1787
80 A	1014-1788
100 A	1014-1789
200 A	1014-1790
40 A	1014-12049
60 A	1014-12050
120 A	1014-12051
150 A	1014-12052
250 A	1014-12053

Technische details

Frequentie	50-60 Hz
Gebruik	Binnen
IP- bescherming	IP20
hoog	65 mm
Breed	48 mm
Lang	30 mm

werktemperatuur	-25 °C~+50 °C
Certificaten	RoHS, CE, UKCA
Merk	MAXGE
Garantie	2 Jaar
Stroomsterkte	40 A, 200 A, 100 A, 80 A, 50 A, 250 A, 150 A, 120 A, 60 A



Beschrijving

Deze transformator heeft een **gesloten kern** voor elektriciteitsnetten. De transformator heeft een sectie van Ø22mm, een isolatiespanning van 0.72kV, aansluitpunten van 6mm², een xxA/5A verhouding en IP20 bescherming. Het kan worden bevestigd op een DIN rail of met een flensen het voldoet aan IEC / EN 60044-1, VDE, BS en UTE regulering.

Stroomtransformator x/5A

Intensiteit (A)

Vermogen (VA)

Primair cl 0.5 cl 1 cl 3 40/50 - - 1,2 60 - - 1,5 80 - 1 2,5 100 - 1.5 3 120 - 2 4 150 1 3 5 200 1 1,5 2 250 1 1,5 3

Referentie:

50 A - TAT022050X05

80 A - TAT022080X05

100 A - TAT022100X05

200 A - TAT022200X05

40 A - TAT022040X05

60 A - TAT022060X05

120 A - TAT022120X05

150 A - TAT022150X05

250 A - TAT022250X05



Extra foto's

