





## Models

| Colour Temperature  |                          | Ref:         |
|---|--------------------------|--------------|
|  | Cool White 6000K - 6500K | 64923-126919 |
|  | Daylight 4000K           | 64923-126923 |

## Technical Details

|                                  |                 |
|----------------------------------|-----------------|
| <b>Power</b>                     | 18 W            |
| <b>Tension</b>                   | 220-240V AC     |
| <b>Frequency</b>                 | 50-60 Hz        |
| <b>Electric Insulation Class</b> | I               |
| <b>Adjustable</b>                | No              |
| <b>Light Source</b>              | EPISTAR SMD2835 |
| <b>LED number</b>                | 90              |
| <b>Brightness</b>                | 1476 lm         |
| <b>Type of Lens</b>              | Frost           |
| <b>Use</b>                       | Indoor, Outdoor |
| <b>IP Protection</b>             | IP65            |
| <b>IK Protection</b>             | IK04            |

|  |                      |
|--|----------------------|
| <b>Material</b>                              | Pc                   |
| <b>Installation</b>                          | Surface              |
| <b>High</b>                                  | 600 mm               |
| <b>Wide</b>                                  | 66 mm                |
| <b>Lenght</b>                                | 58 mm                |
| <b>Useful life</b>                           | 50,000 Hours         |
| <b>Selectable Opening Angle</b>              | 120                  |
| <b>Tube Length</b>                           | 60 cm                |
| <b>Light color</b>                           | Daylight, Cool White |
| <b>Color Temperature</b>                     | 4000K, 6000K - 6500K |
| <b>Energy Efficiency 2023 (EU-2019/2015)</b> | F                    |



## Description

**The 60cm 18W LED Slim Tri-Proof Light is perfect as a replacement for a conventional 40W fluorescent tube**, which allows for 50% savings compared to the conventional luminaire.

### Features of 60cm 18W IP65 LED Slim Tri-Proof Light

The LEDs use SMD2835 technology and along with its 0.95 power factor driver achieves superb luminous efficiency. It is distributed over an opening angle of 120°. Both the housing and the cover of the **Slim Tri-Proof Light are made of polycarbonate, which is a robust material that can withstand high levels of water, dust and corrosion**. All this is summarized in the IP65 and IK04 protection index.

### Applications of 60cm 18W IP65 LED Slim Tri-Proof Light

The design and characteristics of this Tri-Proof Light make it the **perfect solution for the lighting of large and diverse interior spaces, such as factories, warehouses, parking lots, tunnels, terraces...** as well as places where there is humidity.



## Additional photographs

