





## Models

Colour Temperature		Ref:
	Cool White 6000K - 6500K	64920-126912
	Daylight 4000K	64920-126916

## Technical Details

Power	36 W
Tension	220-240V AC
Frequency	50-60 Hz
Electric Insulation Class	I
Adjustable	No
Light Source	EPISTAR SMD2835
Color Rendering Index (CRI)	75
Brightness	2952 lm
Type of Lens	Frost
Use	Indoor, Outdoor

IP Protection	IP65
IK Protection	IK04
Material	Pc
Installation	Surface
Useful life	50,000 Hours
Tube Length	120 cm
Selectable Opening Angle	120
Light color	Daylight, Cool White
Color Temperature	4000K, 6000K - 6500K
Energy Efficiency 2023 (EU-2019/2015)	F



## Description

**The 120cm 36W LED Slim Tri-Proof Light is perfect as a replacement for a conventional 72W fluorescent tube**, which allows for 50% savings compared to the conventional luminaire.

### Features of 120cm 36W IP65 LED Slim Tri-Proof Light

The LEDs use SMD2835 technology and along with its 0.98 power factor driver achieves superb luminous efficiency. It is distributed over an opening angle of 120°. Both the housing and the cover of the **Slim Tri-Proof Light are made of polycarbonate, which is a robust material that can withstand high levels of water, dust and corrosion**. All this is summarized in the IP65 and IK04 protection index.

### Applications of 120cm 36W IP65 LED Slim Tri-Proof Light

The design and characteristics of this Tri-Proof Light make it the **perfect solution for the lighting of large and diverse interior spaces, such as factories, warehouses, parking lots, tunnels, terraces...** as well as places where there is humidity.



## Additional photographs

