

Models

Colour Temperature	Ref:
Warm White 2800K - 3200K	519-1231
Cool White 4000K - 4500K	519-1232
Daylight 5000K - 5500K	519-204926
Daylight 6000K - 6500K	519-1233

Technical Details

Power:	24 W
Voltage:	220-240V AC
Multi-Voltage:	85-265V AC
Frequency:	50-60 Hz
Driver Output:	30-38V DC // 550-600 mA
Protection Class:	II
Light Source:	OSRAM
CRI:	80
Lumens:	1900 lm
Energy Efficiency 2021 (UE-1369/2017):	A
Energy Efficiency 2023 (UE-2019/2015):	F
Beam Angle:	120º
Lens Type:	Frost
Use:	Indoor

IP Protection:	IP20
Material:	Aluminium
Installation:	Surface
Size:	40xØ300 mm
Height:	40 mm
Diameter:	Ø300 mm
Total Weight:	0.72 Kg
Frame:	White
Working Temperature:	-22ºC ~ +45ºC
Includes:	Driver
Life Span:	40,000 Hours
Warranty:	3 Years
Certifications:	CE & RoHS, UKCA

Description

This Round 24W LED Surface Panel Ø300 mm combines design, power and an extremely low consumption into a luminaire that's very easy to install.

It can easily replace a conventional 150W surface panel and **is highly recommendable for use in any area of the home or office, hotel receptions and bars**. It stands out for its light quality, which reproduces colours as they appear naturally and also shows off the items high Colour Rendering Index.

Advantages of this Round 24W LED Surface Panel Ø300 mm
The main advantages are the **high savings in consumption and maintenance** that it provides. It's a simple installation and only requires two screws to hold the support found on the back of the unit onto the ceiling. It's connected directly to the mains using the driver that's included.

Enjoy excellent indoor LED lighting straight from LEDKIA, our online lighting shop.

Includes Driver.

Dimmable.

To dim this panel, purchase the corresponding dimmable driver.

Additional photographs








