



## Models

Box Format	Colour Temperature	Ref:
	<input type="checkbox"/> Daylight 4000K - 4500K	5615-12668





## Technical Details

<b>Power</b>	34 W	<b>High</b>	44 mm
<b>Tension</b>	220-240V AC	<b>Wide</b>	597 mm
<b>Frequency</b>	50-60 Hz	<b>Lenght</b>	597 mm
<b>Electric Insulation Class</b>	II	<b>Room Temperature Work</b>	-22 °C~+45 °C
<b>Adjustable</b>	No	<b>Includes</b>	Driver
<b>Brightness</b>	3200 lm	<b>Useful life</b>	30,000 Hours
<b>Use</b>	Indoor	<b>Brand</b>	PHILIPS
<b>IP Protection</b>	IP20	<b>Brand Driver</b>	PHILIPS
<b>IK Protection</b>	IK02	<b>Light color</b>	Daylight
<b>Material</b>	Aluminum	<b>Color Temperature</b>	4000K - 4500K
<b>Installation</b>	False Ceiling	<b>Energy Efficiency 2023 (EU-2019/2015)</b>	F



## Description

This pack is made up of 38W 60x60cm Philips Ledinaire SmartBalance LED Panels (3200lm).



## Additional photographs

