

LED PANELS 60X60CM

## 60x60cm 60W 6000lm High Power LIFUD LED Panel



Technical Data	
Power:	60 W
Power Factor:	0.90
Voltage:	220-240V AC
Multi-Voltage:	100-240V AC
Frequency:	50-60 Hz
Driver Output:	25-42V DC / 1500mA
Protection Class:	II
Dimmable:	No
Light Source:	SMD 4014
Number of LEDs:	42
CRI:	80
Lumens:	6000 lm
Luminous Efficiency:	100 lm/W
Energy Efficiency 2021 (UE-2019/2015):	A+
Energy Efficiency 2023 (UE-2019/2015):	F
Beam Angle:	120°
Lens Type:	Frost
Use:	Indoor
IP Protection:	IP40
IK Protection:	IK02
Special:	High Brightness
Material:	Aluminium
Installation:	False Ceiling
Size:	30x600x600 mm
Height:	30 mm
Width:	600 mm
Length:	600 mm
Frame:	60x60 cm
Working Temperature:	-10°C ~ +40°C
Includes:	Driver
Life Span:	50,000 Hours
Warranty:	3 Years
Certifications:	CE & RoHS

### Product description

The **60x60cm 60W 6000lm High Power LIFUD LED Panel** has an elegant finish, white lacquered aluminium frame and a slim design perfect for false ceilings.

Its high efficiency 4-sided LED lighting system emits a **luminosity of 6000 lumens, equivalent to that emitted by conventional fluorescent panels of up to 100W**, achieving significant energy savings. With an immediate start-up, no noise and no flickering, this LED Panel is perfect for places where you want to maximize the illuminated space, projecting light evenly and without glare.

This **60x60cm 60W 6000lm High Power LIFUD LED Panel** is the ideal choice if you are looking for a **panel with good performance and minimum power consumption**. It is **widely used in offices, shopping centres, hospitals, warehouses, restaurants, supermarkets, museums, etc., as well as in homes and residences**.

\* They are installed in removable false ceilings, to be installed in false ceilings the panel needs the recessed kit and to be installed in ceilings it needs the surface kit or the suspension kit.

