



## Models

| Colour Temperature                                                                                         | Ref:       |
|------------------------------------------------------------------------------------------------------------|------------|
|  Warm White 2800K - 3200K | 516-1216   |
|  Cool White 4000K - 4500K | 516-1217   |
|  Daylight 5000K - 5500K   | 516-205001 |
|  Daylight 6000K - 6500K   | 516-1218   |

## Technical Details

|                                               |             |
|-----------------------------------------------|-------------|
| <b>Power:</b>                                 | 48 W        |
| <b>Power Factor:</b>                          | 0.90        |
| <b>Voltage:</b>                               | 220-240V AC |
| <b>Multi-Voltage:</b>                         | 85-265V AC  |
| <b>Frequency:</b>                             | 50-60 Hz    |
| <b>Protection Class:</b>                      | II          |
| <b>Light Source:</b>                          | OSRAM       |
| <b>CRI:</b>                                   | 80          |
| <b>Lumens:</b>                                | 3800 lm     |
| <b>Energy Efficiency 2021 (UE-1369/2017):</b> | A           |
| <b>Energy Efficiency 2023 (UE-2019/2015):</b> | F           |
| <b>Beam Angle:</b>                            | 120°        |
| <b>Lens Type:</b>                             | Frost       |
| <b>Use:</b>                                   | Indoor      |

|                             |                 |
|-----------------------------|-----------------|
| <b>IP Protection:</b>       | IP20            |
| <b>Material:</b>            | Aluminium       |
| <b>Installation:</b>        | Surface         |
| <b>Size:</b>                | 35x600x600 mm   |
| <b>Height:</b>              | 35 mm           |
| <b>Width:</b>               | 600 mm          |
| <b>Length:</b>              | 600 mm          |
| <b>Frame:</b>               | White           |
| <b>Working Temperature:</b> | -22°C ~ +45°C   |
| <b>Includes:</b>            | Driver          |
| <b>Life Span:</b>           | 40,000 Hours    |
| <b>Warranty:</b>            | 3 Years         |
| <b>Certifications:</b>      | CE & RoHS, UKCA |



## Description

This **Square 48W LED Surface Panel 600x600 mm** is easy to install on any type of ceiling, be it plaster, concrete or any other surface. It has a 120° opening angle and provides a very evenly distributed light.

Recommended for buildings that are either under construction or have just been completed, they can replace existing light bulbs in homes, offices, waiting rooms, bars, etc.

Includes Driver.

Dimmable.

To dim this panel, purchase the corresponding dimmable driver.



## Additional photographs

