



Models

Power (W)

Ref:

☐ 40 W

65705-131250



Technical Details

Power:	40 W	Material:	PC, Aluminium
Power Factor:	0.97	Size:	21x30x355 mm
Frequency:	50-60 Hz	Height:	21 mm
Input:	100-240V AC	Width:	30 mm
Output:	30-40V DC / 1000mA	Length:	355 mm
Protection Class:	II	Warranty:	5 Years
Use:	Indoor	Certifications:	CE & RoHS, TÜV, ENEC
IP Protection:	IP20	Brand:	LIFUD
Flicker Free:	YES		



Description

Driver made by the prestigious company **LIFUD**, specially designed for emergency situations where it is necessary that, in case of a power failure, it fulfills the lighting requirements in normal and emergency situations. To determine whether a driver will work with our luminaires, PCBs or panels, please consult the voltage and output current of the driver.

Characteristics of the 100-277V LIFUD Flicker-Free Emergency Driver 30-40V Output 1000mA 40W LF-GSP040YD

This **40W 30-40V DC Output Flicker-Free LIFUD Emergency Driver** has a multi-voltage input. This means that it is able to withstand line voltage surges and dips for a short period of time without damage. In addition, **its output is 30V-40V DC 1000mA in Normal Mode and 30-40V DC 350mA in Emergency Mode.**

When there is a power failure, this emergency driver switches to emergency mode and provides **60 to 90 minutes** of illumination depending on the power of the luminaire.

For perfect operation, this product should be powered by a 18V DC LITHIUM Emergency Driver Battery (not included).

This LIFUD Driver features Flicker-Free technology, preventing light flicker and therefore reducing eye fatigue.

Say goodbye to eye fatigue, headaches and blurred vision caused by flickering light.



Additional photographs

