






Models

Colour Temperature	Ref:
 Warm White 2800K - 3200K	1195-2246
 Cool White 4000K - 4500K	1195-2248
 Daylight 6000K - 6500K	1195-2247

Technical Details

Power:	15 W	IK Protection:	IK05
Voltage:	220-240V AC	Material:	Aluminium
Multi-Voltage:	85-265V AC	Installation:	Recessed
Frequency:	50-60 Hz	Size:	20x200x200 mm
Driver Output:	54-75V DC//300 mA	Cut-Out	Ø180x180 mm
Protection Class:	II	Height:	20 mm
Light Source:	OSRAM	Width:	200 mm
Light Colour:	Warm White, Daylight, Cool White	Length:	200 mm
CRI:	80	Total Weight:	0.315 kg
Lumens:	1200 lm	Frame:	Silver
Energy Efficiency 2021 (UE-1369/2017):	A	Working Temperature:	-20°C ~ +45°C
Energy Efficiency 2023 (UE-2019/2015):	F	Includes:	Driver
Beam Angle:	120°	Life Span:	40,000 Hours
Lens Type:	Frost	Warranty:	3 Years
Use:	Indoor	Certifications:	CE & RoHS, UKCA
IP Protection:	IP20		



Description

This Silver Square 15W UltraSlim LED Panel can be used in all sorts of environments, be it in homes or businesses.

Characteristics of this Silver Square 15W UltraSlim LED Panel

It incorporates LED's with SMD2835 technology, which have an 80lm/W performance. **The light is distributed over a 120° beam angle**, which is perfect for general lighting. It's wired direct to 220-240V AC mains and does not require an earth wire. It also has a working life that's 10x times longer than that of a conventional downlight.

The aluminium dissipater that this Silver Square 15W UltraSlim LED Panel features allows heat to be very efficiently distributed. This allows the unit to **work in temperatures ranging from -22°C to 45°C without a problem**.

Here at LEDKIA, our online lighting shop, you'll find the LED downlight that best adjusts to your needs.



Additional photographs

