



Models

Colour Temperature

Ref:

☒ Daylight 6000K

1963-3182



Technical Details

| | |
|--|-----------------|
| Power: | 40 W |
| Voltage: | 220-240V AC |
| Multi-Voltage: | 100-240V AC |
| Frequency: | 50-60 Hz |
| Dimmable: | 1-10 V |
| Light Source: | EPISTAR SMD2835 |
| CRI: | 80 |
| Lumens: | 3600 lm |
| Luminous Efficiency: | 90 lm/W |
| Energy Efficiency 2021 (UE-1369/2017): | A+ |
| Energy Efficiency 2023 (UE-2019/2015): | F |
| Beam Angle: | 120° |
| Lens Type: | Frost |

| | |
|-----------------|-----------------|
| Use: | Indoor |
| IP Protection: | IP40 |
| Material: | PC, Aluminium |
| Colour: | Grey |
| Installation: | Surface |
| Size: | 1190x75x54 mm |
| Height: | 54 mm |
| Width: | 75 mm |
| Length: | 1190 mm |
| Life Span: | 40,000 Hours |
| Warranty: | 5 Years |
| Certifications: | CE & RoHS, UKCA |



Description

This LED Linear Bar features a high quality aluminium housing that provides excellent thermal conductivity and resistance to high temperatures. It uses an anti-glare frosted diffuser that offers uniform light, it has an dimmable flow and also a 2m pre-wired cable, approximately.

Ready to be suspended (includes an adjustable 1m cable, approx.), this linear bar is perfect for lighting any sort of area, although it's generally used in businesses, homes, expositions, offices and warehouses.

*This product includes a approximately 2m pre-wired cable.



Additional photographs

