




## Models

Colour Temperature	Ref:
 Warm White 2700K - 3200K	406-766
 Daylight 4000K - 4500K	406-767
 Cool White 6000K - 6500K	406-768
 Cool White 5000K - 5500K	406-205026

## Technical Details

<b>Power</b>	12 W	<b>Installation</b>	Surface
<b>Tension</b>	220-240V AC	<b>High</b>	40 mm
<b>Rated Voltage</b>	85-265V AC	<b>Wide</b>	170 mm
<b>Frequency</b>	50-60 Hz	<b>Lenght</b>	170 mm
<b>Electric Insulation Class</b>	II	<b>Room Temperature Work</b>	-22 °C~+45 °C
<b>Adjustable</b>	No	<b>Includes</b>	Driver
<b>Light Source</b>	OSRAM	<b>Useful life</b>	40,000 Hours
<b>Color Rendering Index (CRI)</b>	80	<b>Selectable Opening Angle</b>	120
<b>Brightness</b>	880 lm	<b>Light color</b>	Cool White, Daylight, Warm White
<b>Type of Lens</b>	Frost	<b>Color Temperature</b>	5000K - 5500K, 6000K - 6500K, 4000K - 4500K, 2700K - 3200K
<b>Use</b>	Indoor	<b>Energy Efficiency 2023 (EU-2019/2015)</b>	F
<b>IP Protection</b>	IP20	<b>Revisión Control de Calidad</b>	No
<b>Material</b>	Aluminum		



## Description

This Square 18W LED Surface Panel 170x170 mm, whose main feature is its ease of installation on any type of ceiling, be it plaster, concrete or any other surface, has a 120° opening angle and provides a very evenly distributed light.

Recommended for buildings that are either under construction or have just been completed, they can replace existing light bulbs in homes, offices, waiting rooms, bars, etc.

Includes Driver.

Dimmable.

To dim this panel, purchase the corresponding dimmable driver.



## Additional photographs

