






Models

Colour Temperature	Ref:
 Warm White 3000K - 3500K	3628-8207
 Daylight 4000K	3628-8208
 Cool White 6000K	3628-8209



Technical Details

Power	50 W	IK Protection	IK08
Tension	220-240V AC	Material	Crystal, Aluminum
Frequency	50-60 Hz	Installation	Surface
Electric Insulation Class	I	High	235 mm
Adjustable	No	Wide	163 mm
Light Source	SMD2835	Lenght	36 mm
Brightness	5000 lm	Useful life	60,000 Hours
Luminous Efficiency	100 lm/W	Selectable Opening Angle	110
LED Performance	120 lm/W	Light color	Cool White, Daylight, Warm White
Type of Lens	Transparent	Color Temperature	6000K, 4000K, 3000K - 3500K
Use	Outdoor	Energy Efficiency 2023 (EU-2019/2015)	F
IP Protection	IP65		



Description

This White 50W Slim LED Floodlight stands out for its compact design and minimalist finish.

Characteristics of this White 50W Slim LED Floodlight

This White 50W aSlim LED Floodlight is small and has modern and functional design.

Its SMD2835 optic is very efficient. The light is distributed over a 110° angle and is perfect for lighting in all sorts of settings. **It offers considerable energy savings.**

It's designed for lighting outdoor areas **and has IP65 Protection**. It's made of high quality aluminium, which can contribute to efficiently eliminating heat that is generated.

Applications for this White 50W Slim LED Floodlight

It's mainly used on balconies, terraces and gardens, where we want to reduce energy consumption without sacrificing light quality.

Enjoy this White 50W Slim LED Floodlight at the best price at LEDKIA, our online lighting shop.

*This product is pre-wired with a 300mm cable. approximately.



Additional photographs

