



## Models

Colour Temperature	Ref:
<input type="checkbox"/> Cool White 4000K - 4500K	3062-6152
<input checked="" type="checkbox"/> Daylight 6000K - 6500K	3062-6153



## Technical Details

<b>Power:</b>	20 W	<b>IP Protection:</b>	IP20
<b>Power Factor:</b>	0.95	<b>IK Protection:</b>	IK05
<b>Voltage:</b>	220-240V AC	<b>Material:</b>	PMMA, Aluminium
<b>Frequency:</b>	50-60 Hz	<b>Colour:</b>	White
<b>Intensity Level:</b>	0.097 A	<b>Installation:</b>	Surface
<b>Protection Class:</b>	I	<b>Size:</b>	300x300x80 mm
<b>Light Source:</b>	EPISTAR SMD2835	<b>Height:</b>	300 mm
<b>Number of LEDs:</b>	108	<b>Width:</b>	300 mm
<b>CRI:</b>	82	<b>Length:</b>	80 mm
<b>Lumens:</b>	1600 lm	<b>Driver:</b>	LIFUD
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A+	<b>Life Span:</b>	40,000 Hours
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F	<b>Warranty:</b>	5 Years
<b>Beam Angle:</b>	100°	<b>Certifications:</b>	CE & RoHS, UKCA
<b>Lens Type:</b>	Frost	<b>Brand Component</b>	LIFUD
<b>Use:</b>	Indoor		



## Description

This L-shaped Linear Bar features an aluminium housing that provides excellent thermal conductivity and is greatly resistant to high temperatures. Mounted is an anti-glare opal (frosted) diffuser that's made from PMMA, offering homogeneous lighting and reducing visual disturbances.

Especially designed as **an accessory for Turner LED Linear Bars**, as this L-shaped Bar allows us to create our own custom lighting structures.

Light with style thanks to this Linear LED Bar that offers many decorative and lighting possibilities in any location, being widely used in businesses, showrooms, homes, industries and offices.

\*Featuring a LIFUD Driver.



## Additional photographs

