

Ref: 1948





Models

Technical Details

Power:	2 W	IP Protection:	IP65
Voltage:	220-240V AC	Installation:	Surface, Recessed
Frequency:	50-60 Hz	Size:	Ø170x65 mm
Protection Class:	II	Cut-Out	Ø145x48 mm
Light Source:	SMD2835	Working Temperature:	0 °C ~ 40 °C
Number of LEDs:	54	Battery operated:	Yes
Light Colour:	Daylight	Battery:	Li-ion
Colour Temp:	6000K - 6500K	Battery Voltage:	3.7 V
Lumens:	175 lm	Battery Capacity:	2600 mAh
Energy Efficiency 2021 (UE-	A++	Range:	3 Hours
1369/2017):		Life Span:	40,000 Hours
Energy Efficiency 2023 (UE- 2019/2015):	F	Warranty:	3 Years
		Certifications:	CE & RoHS, UKCA
Emergency Lighting:	Non-permanent		
Use:	Outdoor		





Description

This LED Downlight acts as an emergency light and provides high brightness when activated. Featuring a tightly sealed housing with IP65 Protection, its linear beam angle is especially designed for efficiently lighting hallways without wasting light and providing excellent benefits.

Includes protection fuses and an internal battery that lasts 3 hours.

Designed to be either recessed or surface-mounted, it's the most simple, practical and economical solution for any emergency lighting network.

Note:

*Non-Permanent light

*LED Status Indicator.

*To correctly function as an emergency light, connect the pre-wired battery.





Additional photographs





