



### Models

Colour Temperature	Ref:
 Warm White 2800K - 3200K	412-780
 Cool White 4000K	412-1586
 Daylight 5000K - 5500K	412-204929
 Daylight 6000K - 6500K	412-781

### Technical Details

<b>Power:</b>	9 W	<b>IK Protection:</b>	IK05
<b>Voltage:</b>	220-240V AC	<b>Flicker Free:</b>	YES
<b>Multi-Voltage:</b>	85-265V AC	<b>Material:</b>	Aluminium
<b>Frequency:</b>	50-60 Hz	<b>Installation:</b>	Recessed
<b>Protection Class:</b>	II	<b>Size:</b>	20xØ142 mm
<b>Light Source:</b>	OSRAM	<b>Cut-Out</b>	Ø130 mm
<b>Light Colour:</b>	Daylight, Cool White, Warm White	<b>Height:</b>	20 mm
<b>CRI:</b>	80	<b>Diameter:</b>	Ø142 mm
<b>Lumens:</b>	700 lm	<b>Total Weight:</b>	0.155 kg
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A	<b>Frame:</b>	White
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F	<b>Working Temperature:</b>	-22°C ~ +45°C
<b>Beam Angle:</b>	120°	<b>Includes:</b>	Driver
<b>Lens Type:</b>	Frost	<b>Life Span:</b>	40,000 Hours
<b>Use:</b>	Indoor	<b>Warranty:</b>	3 Years
<b>IP Protection:</b>	IP20	<b>Certifications:</b>	CE & RoHS, UKCA



## Description

The **9W Round Ultraslim LED Panel Ø 130mm Cut-Out** is ideal as a general lighting element in all types of spaces, both commercial and domestic.

### Features of the 9W Round Ultraslim LED Panel Ø 130mm Cut-Out

The SMD 2835 LED source has an efficiency of 80 lm/W. **It operates directly at 220-240V AC without the need for connection to the installation's earth.** It can withstand input voltage fluctuations between 85 and 265V AC.

Made of aluminium, the 9W SuperSlim circular **LED panel dissipates heat very efficiently**, despite being so compact. All this allows it to operate correctly in a range of ambient working temperatures from -22° to 45°C.

\*It is recommended to make a minimum cut of Ø133 mm.



### Additional photographs

