





Models

Colour Temperature		Ref:
	Cool White 6000K	65123-173431
	Daylight 4000K - 4500K	65123-173435

Technical Details

Power	18 W
Tension	220-240V AC
Rated Voltage	100-265V AC
Frequency	50-60 Hz
Electric Insulation Class	I
Adjustable	No
Color Rendering Index (CRI)	80
Brightness	1620 lm
Luminous Efficiency	90 lm/W
Type of Lens	Frost
Use	Indoor, Outdoor
IP Protection	IP65

IK Protection	IK04
Material	Pc
Installation	Surface
High	70 mm
Wide	70 mm
Useful life	40,000 Hours
Selectable Opening Angle	120
Tube Length	60 cm
Light color	Daylight, Cool White
Color Temperature	4000K - 4500K, 6000K
Energy Efficiency 2023 (EU-2019/2015)	F



Description

The **60cm 18W Integrated LED Linkable Tri-Proof Kit IP65** with a rectangular design and **18W of power**. It offers optimum results both in terms of light and waterproofing, **thanks to its materials and design that make it water, dust and corrosion resistant, with an IP65 protection rating**. It has a PC housing and a PC cover. It is ideal for the replacement of conventional screens with 40W fluorescent tubes. This product stands out for its ability to connect multiple units in series to create a continuous and uniform lighting solution. This functionality is ideal for projects requiring extensive light coverage, as it allows multiple displays to be powered from a single power source, simplifying installation and reducing the need for additional cabling.

The design and characteristics of the LED Tri-Proof Kit make it **ideal to install in a wide range of facilities such as factories, warehouses, car parks, tunnels, terraces... as well as places with humidity**.

* Linkable up to 8 units.



Additional photographs

