






Models

Colour Temperature	Ref:
 Warm White 2700K	63048-123452
 Cool White 4000K	63048-123456
 Daylight 6000K	63048-123460



Technical Details

Power:	10 W	UGR (Glare Rating):	UGR 19
Power Factor:	0.90	Special:	Low UGR
Voltage:	220-240V AC	Flicker Free:	YES
Frequency:	50-60 Hz	Material:	PC
Protection Class:	II	Installation:	Recessed
Light Source:	LUMILEDS SMD5050	Size:	60xØ125 mm
CRI:	85	Cut-Out	Ø105 mm
Lumens:	1000 lm	Height:	60 mm
Luminous Efficiency:	100 lm/W	Diameter:	Ø125 mm
Energy Efficiency 2021 (UE-1369/2017):	A+	Total Weight:	0.11 kg
Energy Efficiency 2023 (UE-2019/2015):	F	Working Temperature:	-20°C ~ +40°C
Beam Angle:	100°	Life Span:	50,000 Hours
Lens Type:	Frost	Warranty:	5 Years
Use:	Indoor	Certifications:	CE & RoHS, UKCA
IP Protection:	IP44		



Description

The Lux 10W LED Downlight IP44 No Flicker with Ø 105 mm Cut-Out features a **modern and compact design** that with its integrated driver allows direct connection to the mains. Its main elements such as the **front ring, heatsink and reflector are constructed of high purity aluminum with the highest quality finishes.**

Features of The Lux 10W LED Downlight IP44 No Flicker with Ø 105 mm Cut-Out

It incorporates a **LUMILEDS brand light source with SMD3030 technology** that provide a **performance of 100 Lm/W**. It emits a **high quality light**, as indicated by its high **color rendering index preventing color distortion**, in a beam width of 90°. So it is ideal for product exposure. **The IP44 factor indicates** that it is especially protected against dust and splashes. Ensuring a **lifespan of 30,000 hours.**

The Lux 10W LED Downlight IP44 No Flicker with Ø 105 mm Cut-Out features a glare factor UGR<19 to ensure uniform light without glare, making it ideal for work areas such as offices, conference rooms, classrooms, libraries, etc.

Advantages of the Lux 10W LED Downlight IP44 No Flicker with Ø 105 mm Cut-Out

Its installation is extremely simple, both for the **integrated driver** it owns and for its lightness. It only requires a **cut of 95mm diameter** on the surface to be installed.

Thanks to the features of this downlight you can use almost anywhere whether in shops, museums, shopping centers, hotels, supermarkets, restaurants, etc., although it can be used in various areas outside the tertiary sector such as stairs, halls, corridors... Or as a complement to general lighting in offices, conference rooms, classrooms, libraries, etc.

In our online lighting shop you will find the Lux 10W LED Downlight IP44 No Flicker with Ø 105 mm Cut-Out in **different color temperatures and different powers**, with all the confidence offered by **CE and RoHS certificates** and the **two years warranty** we offer you.



Additional photographs

