



Models

Colour Temperature	Ref:
 Warm White 2800K - 3200K	438-929
 Cool White 4000K - 4500K	438-930
 Daylight 5000K - 5500K	438-204919
 Daylight 6000K - 6500K	438-931

Technical Details

Power:	18 W	IK Protection:	IK05
Voltage:	220-240V AC	Material:	Aluminium
Multi-Voltage:	85-265V AC	Installation:	Recessed
Frequency:	50-60 Hz	Size:	20xØ225 mm
Protection Class:	II	Cut-Out	Ø205 mm
Light Source:	OSRAM	Height:	20 mm
Light Colour:	Daylight, Cool White, Warm White	Diameter:	Ø225 mm
CRI:	80	Total Weight:	0.3 kg
Lumens:	1400 lm	Frame:	Silver
Energy Efficiency 2021 (UE-1369/2017):	A	Working Temperature:	-20°C ~ +45°C
Energy Efficiency 2023 (UE-2019/2015):	F	Includes:	Driver
Beam Angle:	120°	Life Span:	40,000 Hours
Lens Type:	Frost	Warranty:	3 Years
Use:	Indoor	Certifications:	CE & RoHS, UKCA
IP Protection:	IP20		



Description

The Silver Round 18W UltraSlim LED panel has an ultra-thin and modern design, with an elegant silver lacquered aluminium finish.

Featuring SMD2835 LEDs, this panel has a luminous output of 1,400 lumens, equivalent to the brightness of a 36W low-power downlight. **Its high colour rendering index of over 80 ensures optimum colour rendering.** Its lifespan is extended to 30,000 working hours.

Applications of the Silver Round 18W UltraSlim LED panel

Although it can be used in commercial spaces without problems, this type of LED lighting is commonly used for general lighting in residential areas. Its wide beam angle of 120° **distributes the light very evenly and its opal diffuser reduces glare.**

Check out the Silver 18W UltraSlim LED panel available in various colour temperatures to choose from like cool white, daylight or warm white here at LEKDIA.



Additional photographs

