



Models



Technical Details

Maximum Power:	300 W
Voltage:	220-240V AC
Frequency:	50-60 Hz
Protection Class:	II
Beam Angle:	360°
Use:	Indoor
IP Protection:	IP20
Material:	PCB
Installation:	Recessed
Size:	75xØ80 mm

Cut-Out	Ø60 mm
Height:	75 mm
Diameter:	Ø80 mm
Total Weight:	0.09 Kg
Detector:	Radar
Detection Distance:	8 m
Detection Angle:	360°
Working Temperature:	-20°C ~ +40°C
Warranty:	3 Years
Certifications:	CE & RoHS, UKCA



Description

This Motion Sensor, which can be recessed in the ceiling, has a 360° coverage angle and a 1 to 8 metre detection field when installed at a height of 1.5 to 3.5 metres.

The detector activates its output circuit when motion is detected within its range and deactivates when the movement is no longer detected, after an adjustable amount of time. It includes a detection distance regulator, light sensitivity (day/night) and a timer.

Detection angle: 360°

Detection distance: a 1 to 8 metre radius.

Minimum power-ON time: 10 seconds \pm 3 seconds.

Minimum power-OFF time: 12 minutes \pm 1 minute.

Installation height: 1.5 to 3.5 metres.

Detection speed: 0.6-1.5 m/s.

Charges: 300W LED and 1200W Incandescent.



Additional photographs

