



Models



Technical Details

Tension	220-240V AC
Frequency	50-60 Hz
Electric Insulation Class	II
Use	Indoor
IP Protection	IP20
Material	Pc
High	22 mm

Wide	88 mm
Lenght	38 mm
Tensión Driver	39 V-65 V
Maximum Driver Intensity	300 mA
Minimum Driver Tension	39 V
Maximum Driver Tension	65 V



Description

This **Universal driver** is specially designed for **LED panels and recessed or surface mounted LED downlights because it incorporates a jack connector**. An LED driver is responsible for transforming the alternating current from the mains into direct current capable of illuminating the LED chips. To know if a driver is going to work with our luminaire, PCB or panel you should consult the voltage and the output current of the driver.

Characteristics of the 18W 39-65V Output 90-265V 300mA Driver

This driver has a multi-voltage input. This means that it is able to withstand high and low line-voltage for a short period of time without damage. In addition, its **output** is also **multi-voltage** which means that it can deliver constant voltage within a range allowing the same driver to be used for various applications with different current and voltage requirements. Once the driver is powered, the voltage will be automatically adjusted and the output voltage will be constant. Its power factor is very high, making it a very efficient driver.

Discover our wide range of drivers available at **Ledkia**, our online LED shop.



Additional photographs

