



o Ledkia.

## Models

Flicker	Color Temperature	Ref
No Flicker		





## **Technical Details**

Power	14 W
Tension	220-240V AC
Frequency	50-60 Hz
Electric Insulation Class	II
Light Source	SMD2835
Color Rendering Index (CRI)	80
Brightness	1400 lm
Luminous Efficiency	100 lm/W
Use	Indoor
IP Protection	IP40
Material	Pc

Wide 22 mm  Lenght 875 mm  Useful life 40,000 Hours  Selectable Opening Angle 120  Tube Length 90 cm  Light color Daylight, Warm White, Cool White  Color Temperature 4000K, 3200K, 6500K  Energy Efficiency 2023 (EU-2019/2015)  Flicker No Flicker	High	35 mm
Useful life 40,000 Hours  Selectable Opening Angle 120  Tube Length 90 cm  Light color Daylight, Warm White, Cool White  Color Temperature 4000K, 3200K, 6500K  Energy Efficiency 2023 (EU-2019/2015)	Wide	22 mm
Selectable Opening Angle  Tube Length 90 cm  Light color Daylight, Warm White, Cool White  Color Temperature 4000K, 3200K, 6500K  Energy Efficiency 2023 (EU-2019/2015)  F	Lenght	875 mm
Tube Length 90 cm  Light color Daylight, Warm White, Cool White  Color Temperature 4000K, 3200K, 6500K  Energy Efficiency 2023 (EU-2019/2015)	Useful life	40,000 Hours
Light color  Color Temperature  4000K, 3200K, 6500K  Energy Efficiency 2023 (EU-2019/2015)  Daylight, Warm White, Cool White  4000K, 3200K, 6500K	Selectable Opening Angle	120
Color Temperature       4000K, 3200K, 6500K         Energy Efficiency 2023 (EU-2019/2015)       F	Tube Length	90 cm
Energy Efficiency 2023 (EU- 2019/2015)	Light color	Daylight, Warm White, Cool White
2019/2015)	Color Temperature	4000K, 3200K, 6500K
Flicker No Flicker	<b>3,</b> , ,	F
	Flicker	No Flicker





## **Description**

The 90cm 14W LED Batten with Linkable Switch offers a lighting solution that combines quality and substantial energy and maintenance savings. The product incorporates a connector to connect several strips in series. It is recommended to join up to a maximum of 5 strips to form a chain of 4.5 meters in length.

It offers very homogeneous lighting thanks to the 120° opening angle of the light beam. The opal finish of the luminaire reduces glare. It has an aluminium housing and a cover made of PC (polycarbonate), materials resistant to water, dust and corrosion. It has a connecting cable to feed the strip. Its driver is integrated inside the strip.

The 90cm 14W LED Batten with Linkable Switch is ideal for replacing traditional terminal blocks and for installation in a wide range of installations such as factories, warehouses, car parks, tunnels, niches or terraces.





## Additional photographs

