



### Models

Colour Temperature	Ref:
<input checked="" type="checkbox"/> Warm White 2800K - 3200K	1137-2111
<input type="checkbox"/> Cool White 4000K - 4500K	1137-2109

### Technical Details

<b>Power:</b>	6 W	<b>Use:</b>	Indoor
<b>Voltage:</b>	220-240V AC	<b>IP Protection:</b>	IP20
<b>Multi-Voltage:</b>	85-265V AC	<b>Material:</b>	Aluminium
<b>Frequency:</b>	50-60 Hz	<b>Installation:</b>	Surface
<b>Driver Output:</b>	14-26V DC // 300 mA	<b>Size:</b>	37xØ120 mm
<b>Protection Class:</b>	II	<b>Height:</b>	37 mm
<b>Light Source:</b>	OSRAM	<b>Diameter:</b>	Ø120 mm
<b>CRI:</b>	80	<b>Frame:</b>	Silver
<b>Lumens:</b>	480 lm	<b>Includes:</b>	Driver
<b>Energy Efficiency 2021 (UE-1369/2017):</b>	A	<b>Life Span:</b>	40,000 Hours
<b>Energy Efficiency 2023 (UE-2019/2015):</b>	F	<b>Warranty:</b>	3 Years
<b>Beam Angle:</b>	120°	<b>Certifications:</b>	CE & RoHS, UKCA
<b>Lens Type:</b>	Frost		



## *Ambience*





## ***Description***

**The 6W Silver Metal Round LED Surface Panel Ø120 mm has a modern design and a very elegant silver finish.**

Its Epistar-SMD2835 light source provides us with a brightness of 480 lumens, which is equivalent to a conventional 40W luminaire. This **provides us with considerable energy savings**. It's used for general lighting in indoor spaces as it has a 120° opening angle.

The technical parameters of this Design Surface Panel make it **a very common LED lighting element in hallways, entrances and stairways**, or in any space in which we require lighting with low consumption.



**Additional photographs**

